





- NOTE:
- 1.MATERIAL SPECIFICATION:
 - 1.HOUSING:LCP.
 - 2.CONTACTS:PHOSPHOR BRONZE,Ni/Au PLATED
 - 3.FRONT SHELL: STAINLESS STEEL,Ni or Sn PLATED
 - 2.MECHANICAL PERFORMANCE,
 - 2-1.INSERTION FORCE: 3.57kgf MAX.
 - 2-2.REMOVAL FORCE: 1.02kgf MIN.
 - 2-3.LIFE: 10000 CYCLES.
 - 3.ELECTRICAL PERFORMANCE,
 - 3-1. CURRENT RATING: 5A
 - 3-2. CONTACT RESISTANCE: 30M Ω MAX
 - 3-3.INSULATION RESISTANCE: 100M Ω MIN
 - 3-4.DIELECTRIC WITHSTAND VOLTAGE,AC 250V
 4. ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: $-25^{\circ}\text{C}\sim+85^{\circ}\text{C}$.

A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

TOLERANCE UNSPECIFIED 10.00mm							APPROVALS		DATE				
							DRAWN						
							CHECKED			TITLE:			
							APPROVALS			PART NO.			
	A		NEW				TOLERANCES ARE	30~100	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ: 
						10~30		±0.25					
						5~10		±0.20					
						~ 5		±0.15					
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.		±2°		DRAWING NO.		SHEET 1 OF 1	